

KENWOOD



TK-5710G/5810G

VHF/UHF FM & Project 25 Digital Mobile Radio



FleetSync[®]
by KENWOOD

GENERAL FEATURES

- 50W & 110W (136-174 MHz)
- 45W & 100 W (450-520, 400-470 MHz)
- 100 Zones / 1024 Channels
- Personality Lists
- Enhanced Kenwood Audio
- Zone/CH Voice Announce
- Emergency Features
- Tactical Group
- Intercom¹
- Public Address
- Time Out Timer
- Busy Channel Lockout
- Ignition Sense²
- Timed Power Off
- DB-25 & 9-Pin Accessory Connectors³
- Transceiver Password
- Date & 12/24 Hour Time Clock
- Windows[®] Programming & Tuning⁴
- Windows[®] Firmware Uploading⁴
- Field-Programming & Tuning
- Cloning
- Easy Option Ports (26-pin)⁵
- Voice Guide & Storage (Option)
- DB-25 & 9-Pin Accessory Connectors
- MIL-STD 810 C/D/E/F, IP-54
- MIL-STD Noise-Cancel Mic
- MIL-STD 12-Key DTMF Mic Option

MOUNTING CONFIGURATIONS

- Dash Mount
- Single Control Head Remote Mount
- Handheld Control Remote Mount
- Dual Control Head Remote Mount

FRONT PANELS/CONTROL HEADS

- Backlit Dot Matrix LCD
- 3-Digit Sub-Display
- Function / Status LCD Icons
- Transmit LED
- Busy/Call Alert/Warn LED
- LCD Brightness Control
- Power On/Off Switch
- Rotary Volume Knob
- Rotary Selector Knob
- Backlit Keys
- PF Key Label Inserts
- Microphone Jack
- MIL-STD 810 512.X Driven Rain

KCH-14 Front Panel

- 12-Character Alphanumeric Aliases
- 5 PF Keys
- UP/DOWN Keys
- Built-in Front Speaker

KCH-15 Front Panel

- 14-Character Alphanumeric Aliases
- 11 PF Keys
- UP/DOWN Keys
- External Speaker Required

KCH-16 Handheld Control Head

- 14-Character Alphanumeric Aliases
- 5 PF Keys & UP/DOWN/LEFT/RIGHT Keys
- Front PF Keys Name Display
- 12-Key DTMF/Function Keypad
- External Speaker Required

SCAN TYPES (FM & P25)

- Single Zone/Multi-Zone Scan¹²
- Scan Lists
- Conventional Scan
- Limited Talk Group Scan⁶
- Priority Monitor Scan⁶
- Dual Priority Scan

FM


- QT / DQT
- Operator Selectable Tone
- Two-Tone Decode / Encode⁷
- DTMF Encode / Decode / Stun⁸
- Special Alert Tone Patterns⁹
- Horn Alert Output
- Encryption / ANI Board Control
- Companded Audio
- FleetSync[®]/II PTT ID / Caller ID Display / Emergency¹⁰
- MDC-1200 PTT ID / Caller ID Display / Emergency¹⁰

P25 DIGITAL

- P25 Digital Conventional
- P25 Digital Trunking Option
- AMBE+2[™] Enhanced VOCODER
- Talk Group ID Lists
- Individual ID Lists
- Caller ID Display
- RSSI Indicator
- Remote Monitor / Remote Check
- Radio Inhibit
- Encryption Key Delete
- Encryption Key Zeroize (SCM required)
- Encryption Key Retention (SCM required)
- DES 16-Key SCM Option
- AES FIPS 140-2 & DES 16-Key SCM Option
- KPG-94 KVL Key Loader Interface Cable¹¹
- P25 GPS Location
- P25 OTAR Option



Options

- KMC-9B**
Desktop Microphone 
- KMC-27**
Microphone (MIL-SPEC noise-canceling) 
- KMC-28**
Keypad Microphone (MIL-SPEC noise-canceling) 
- KCT-18**
Ignition Sense Cable 
- KES-5**
External Speaker (20W) 
- KCH-14**
Basic Remote Control Head 
- KCH-15**
Full-Featured Remote Control Head 
- KCH-16**
Handheld Control Head 
- KRK-5**
Single Control Head Remote Kit 
- KRK-6DH**
Dual Control Head Remote Kit 
- KRK-11**
Handheld Control Head Interface Kit 
- KPG-94**
Keypad Interface Cable 
- VGS-1**
Voice Guide & Storage Unit 

All accessories and options may not be available in all markets. Contact an authorized Kenwood dealer for details and complete list of all accessories and options.

Specifications

Model	TK-5710G	TK-5710HG	TK-5810G	TK-5810HG
GENERAL				
Frequency Range	136-174 MHz		450-520 MHz	
Type 1			400-470 MHz	
Type 2				
Number of Channels			1024	
Zones			100	
Max. Channels per Zone			512	
Channel Spacing	12.5 / 15 / 20 / 25 / 30 kHz		12.5 / 25 kHz	
Analog				
Digital			12.5 kHz	
Operating Voltage	13.6V DC ± 15%	13.4V DC ± 15%	13.6V DC ± 15%	13.4V DC ± 15%
Current Drain			Less than 0.6A	
Standby			Less than 2.3A	
Receive				
Transmit	Less than 12A	Less than 25A	Less than 14A	Less than 28A
Duty Cycle			Transmit: 20%	
Operating Temperature Range	-22 °F to +140 °F (-30 °C to +60 °C)			
Frequency Stability	± 2.0 ppm (-22 °F to +140 °F)			
Antenna Impedance	50 Ω			
Dimensions (W x H x D)				
RF Deck only	7.01 x 2.36 x 7.68 in. (178 x 60 x 195 mm)	7.01 x 2.36 x 12.87 in. (178 x 60 x 327 mm)	7.01 x 2.36 x 7.68 in. (178 x 60 x 195 mm)	7.01 x 2.36 x 12.87 in. (178 x 60 x 327 mm)
with KCH-14 or15	7.05 x 2.36 x 9.09 in. (179 x 60 x 231 mm)	7.05 x 2.36 x 14.29 in. (179 x 60 x 363 mm)	7.05 x 2.36 x 9.09 in. (179 x 60 x 231 mm)	7.05 x 2.36 x 14.29 in. (179 x 60 x 363 mm)
Weight				
RF Deck only	5.3 lbs. (2.4 kg)	8.6 lbs. (3.9 kg)	5.5 lbs. (2.5 kg)	9.2 lbs. (4.2 kg)
with KCH-14	5.9 lbs. (2.7 kg)	9.2 lbs. (4.2 kg)	6.2 lbs. (2.8 kg)	9.9 lbs. (4.5 kg)
with KCH-15	5.9 lbs. (2.7 kg)	9.2 lbs. (4.2 kg)	6.2 lbs. (2.8 kg)	9.9 lbs. (4.5 kg)
FCC ID				
Type 1	K4435753110	K4435753210	K4439923110	K4439923210
Type 2			K4439923120	K4439923220
IC Certification				
Type 1	282F-35753110			
Type 2			282F-39923120	
RECEIVER				
Sensitivity				
Digital (5% BER)			0.25 µV	
Digital (1% BER)			0.40 µV	
Analog 12 dB SINAD			0.25 µV	
Selectivity				
Digital			-63 dB	
Analog @ 25/30 kHz	-83 dB / -85 dB			
Analog @12.5/15 kHz	-76 dB / -80 dB			
Intermodulation Distortion (Digital & Analog)			-80 dB	
Spurious Response (Digital & Analog)			-90 dB	
Audio Distortion				
Digital	Less than 1.0%			
Analog	Less than 2.0%			
Audio Output				
Internal (KCH-14)	@3%	1.5 W at 8 Ω		
	@5%	1.625 W at 8 Ω		
External	@3%	12 W at 4 Ω		
	@5%	13 W at 4 Ω		
TRANSMITTER				
RF Output Power	50 W to 5 W	110 W to 50 W	45 W to 5 W	100 W to 50 W ¹²
Spurious & Harmonics			80 dB	
FM Hum & Noise				
Analog @ 25 kHz	50 (53) ¹¹ dB		50 dB	
Analog @12.5 kHz	45 (47) ¹¹ dB		45 dB	
Microphone Impedance	600 Ω			
Audio Distortion	Less than 2%			
Modulation	16K0F3E, 11K0F3E, 8K10F1E, 8K10F1D 20K0F7D, 11K2F7D, 14K4F1D, 7K20F1D			

Analog measurements made per TIA/EIA 603
Digital measurements made per TIA/EIA 102CAAA

(*) 148MHz ~ 168MHz
(*) Type 1: 100W to 50W for 450-500MHz. More than 60W to 50W for 500-520MHz.
Type 2: 100W to 50W for 400-470MHz.

FleetSync® is a registered trademark of JVC KENWOOD Corporation in the United States and/or other countries.

Windows® is a registered trademark of Microsoft Corporation in the United States and other countries.

AMBE+2™ is a trademark of Digital Voice Systems Inc.

The P25 Logo is used under license and is a registered trademark of the Project 25 Technology Interest Group.

Specifications are subject to change without notice, due to advancements in technology.

Applicable MIL-STD & IP

Standard	MIL 810C Methods/Procedures	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures	MIL 810F Methods/Procedures
Low Pressure	500.1/Procedure I	500.2/Procedure I, II	500.3/Procedure I, II	500.4/Procedure I, II
High Temperature	501.1/Procedure I, II	501.2/Procedure I, II Cat.A1	501.3/Procedure I, II Cat.A1	501.4/Procedure I, II
Low Temperature	502.1/Procedure I	502.2/Procedure I, II Cat.C1	502.3/Procedure I, II Cat.C1	502.4/Procedure I, II
Temperature Shock	503.1/Procedure I	503.2/Procedure I Cat.A1, C1	503.3/Procedure I Cat.A1, C1	503.4/Procedure I, II
Solar Radiation	505.1/Procedure I	505.2/Procedure I	505.3/Procedure I	505.4/Procedure I
Rain	506.1/Procedure I, II	506.2/Procedure I, II	506.3/Procedure I, II	506.4/Procedure I, III
Humidity	507.1/Procedure II	507.2/Procedure II	507.3/Procedure II	507.4
Salt Fog	509.1/Procedure I	509.2/Procedure I	509.3/Procedure I	509.4
Dust	510.1/Procedure I	510.2/Procedure I, II	510.3/Procedure I	510.4/Procedure I, III
Vibration	514.2/Procedure VIII, X	514.3/Procedure I Cat.8, II Cat.3	514.4/Procedure I Cat.8, II Cat.3	514.5/Procedure I Cat.20, II Cat.5
Shock	516.2/Procedure I, II, III, V	516.3/Procedure I, IV, V, VI	516.4/Procedure I, IV, V, VI	516.5/Procedure I, IV, V, VI
International Protection Standard				
Dust & Water Protection	IP54			

Footnotes from Front:

¹ Intercom: Dual Head capable remote mounts only.

² KCT-18 Ignition sense cable option required.

³ DB-25 ACC: I/O's for dispatch consoles, desktop remotes, vehicle intercom/PA units, motorcycle PTT/headset kits, PC Laptop /Data Modems, GPS/AVL Modems, DB-25 (9 Prog. AUX I/O's & 2 Prog. AUX Outputs); 1 Prog Input (on Control Head).

⁴ KPG-95DG Software required (Windows 98/ NT/ 2000/ Me/XP Vista (32 bit) compatible).

⁵ Easy Option Ports: VGS-1, ANI & Scrambler board ports; only 2 ports can be used simultaneously.

⁶ P25 Trunking option required.

⁷ Two-Tone: Decode (4 sets x 4 pairs each); Encode: 32 pairs; Operator Selectable Tone (40 QT.DQT code pairs).

⁸ DTMF Encode: PTT ID, Emergency ANI, Manual Encode (KMC-28), Auto-Dial (9 numbers); DTMF Decode: Primary/Secondary ID, Stun (a.k.a. dead beat disable).

⁹ Operates for 2-Tone, DTMF, FleetSync selective calling.

¹⁰ Either MDC-1200 or FleetSync® can be activated per radio.

¹¹ KPG-94 adapts the Motorola, KVL3000/3000 Plus Key Loader to the TK-5710G/5810G.